



Order form
Orderer _____

Valid from June 2016
Order no. _____

DM70 Hand-held Dewpoint Meter

| Vaisala DRYCAP® Hand-held Dewpoint Meter | | DM70 | | | | | | | PRICE |
|------------------------------------------|---------------------------------------------------------------------------|------|---|---|--|--|---|-------------|-------|
| Indicator type | no indicator* | A | | | | | | | |
| | rechargeable with Euro AC adapter | B | | | | | | | |
| | rechargeable with UK AC adapter | C | | | | | | | |
| | rechargeable with US AC adapter | D | | | | | | | |
| | rechargeable with AUS AC adapter | E | | | | | | | |
| | rechargeable with all AC adapters | F | | | | | | | |
| | alkaline batteries only | K | | | | | | | |
| Indicator accessories | no indicator accessories | 0 | | | | | | | |
| | <i>MI70LINK software with RS232 cable (MI70LINK)</i> | 1 | | | | | | | |
| | <i>analog output-signal cable (27168ZZ)</i> | 2 | | | | | | | |
| | <i>MI70Link with RS232 and analog output signal cables</i> | 3 | | | | | | | |
| | <i>MI70Link software with USB cable (219687)</i> | 5 | | | | | | | |
| Probe type | DMP74A -40...+60 °C Td | A | | | | | | | |
| | DMP74B -60...+20 °C Td | B | | | | | | | |
| | DMP74C -50...+20 °C Td (for SF6 gas) | C | | | | | | | |
| Probe accessories | no accessories | 0 | | | | | | | |
| | <i>sampling cell DSC74</i> | 1 | | | | | | | |
| | <i>portable sampling system with case (DSS70A)</i> | 2 | | | | | | | |
| | <i>sampling cell DMT242SC</i> | 3 | | | | | | | |
| | <i>sampling cell DMT242SC2</i> | 4 | | | | | | | |
| | <i>two-pressure sampling cell DSC74B</i> | 5 | | | | | | | |
| | <i>two-pressure sampling cell with coil DSC74C</i> | 6 | | | | | | | |
| Connection cable to a transmitter | no connection cable | | A | | | | | | |
| | <i>connection cable to DMT242 transmitter (27160ZZ)</i> | | B | | | | | | |
| | <i>connection cable to DMP248 transmitter (27159ZZ)</i> | | C | | | | | | |
| | <i>connection cable to DMT142 transmitter (211917ZZ)</i> | | D | | | | | | |
| | <i>connection cable to DMT340 series transmitter (211339)</i> | | E | | | | | | |
| | <i>connection cable to DMT152, DMT132 and DMT143 transmitter (219980)</i> | | F | | | | | | |
| | <i>connection cables to DMT340 & DMP248 & DMT242 & DMT142</i> | | M | | | | | | |
| Carrying case | no carrying case** | | 0 | | | | | | |
| | <i>carrying case MI70CASE3 (light grey weatherproof hard plastic)</i> | | 3 | | | | | | |
| | <i>soft carrying case (MI70SOFTCASE)</i> | | 4 | | | | | | |
| Manual language | No Manual | | | A | | | | | |
| | English | | | B | | | | | |
| | German | | | C | | | | | |
| | French | | | D | | | | | |
| | Japanese | | | J | | | | | |
| | Chinese | | | L | | | | | |
| Special features | Standard | | | | | | 1 | | |
| | | | | | | | | TOTAL | |
| | | | | | | | | QTY | |
| | | | | | | | | TOTAL VALUE | |

* select item A, if only probe is ordered

** select item 0, if portable sampling system is selected

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code with typical settings:

DM70 B 5 B 1 A 3 B 1

End customer: _____

Accessories:

10m (32.81 ft) extension cable for probe
 Connection cable for DMT242 transmitter
 Connection cable for DMT340 series
 Connection cable for DMT152, DMT132 and DMT143 transmitters
 Connection cable for DMT142 transmitter
 MI70 Link software with USB cable
 MI70 Link software with serial port cable
 Portable sampling system
 Weatherproof hard plastic carrying case
 Soft carrying case

Order code:

213107SP
 27160ZZ
 211339
 219980
 211917ZZ
 219687
 MI70LINK
 DSS70A
 MI70CASE3
 MI70SOFTCASE